

JET 719AS-M Morticer**FEATURES**

- ▶ Toothed rack height adjuster together with accurate dovetail guide and gas pressure balancer cylinder
- ▶ Powerful motor
- ▶ Head can be turned by 180° for drilling a door lock
- ▶ Large-sized handwheels for easy adjustment of the jig table
- ▶ End stops for precision batch productions
- ▶ Workpiece clamp with quick adjustment
- ▶ Enclosed base cabinet with storage compartment
- ▶ Table tilt angle (719-AS-M) up to 35°

**TECHNICAL DATA**

Motor (V / kW)	230 / 1.3
Spindle speeds (rpm)	1'450
Maximum cutter size (hard / soft)	19 × 19 / 25 × 25
Max. bore size diameter (mm)	13
Max. workpiece height (mm)	195
Max. chisel stroke (mm)	200
Table travel along axes (longitudinal / transverse, mm)	400 / 100
Table tilt	0 – 35°
Table size (mm)	520 × 180
Dimensions of the workpiece stop (mm)	520 × 90
Centre of chisel to back fence (mm)	100
Dimensions (mm)	650 × 500 × 1'760
Weight (kg)	125

CONTENT OF DELIVERY

Cabinet stand

13mm drill chuck

Chuck key

Spindle extension

5/8" (15,87mm) chisel bushing

3/4" (19.05mm) chisel bushing

13/16" (20,64mm) chisel bushing

1-3/16" (30,16mm) chisel bushing

2 handwheel handles

MDF table


Operating handle

work stop



JET 719AS-M Stemm-Maschine**FEATURES**

- ▶ Zahnstangenhöhenverstellung in Verbindung mit präziser Schwalbenschwanzführung und Gasdruck-Ausgleichszylinder
- ▶ Leistungsstarker Motor
- ▶ Kopf 180° drehbar, zum Einbohren eines Türschlosses
- ▶ Gross dimensionierte Handräder für leichte Einstellung des Koordinatentisches
- ▶ Endanschläge für präzise Serienproduktionen
- ▶ Werkstückspanner mit Schnellverstellung
- ▶ Geschlossener Unterschrank mit Ablagefach
- ▶ Tischneigung bis 35° (719-AS-M)

**TECHNISCHE DATEN**

Motor (V / kW)	230 / 1.3
Spindeldrehzahl (U / min)	1'450
Max. Meisselgrösse (Hartholz / Weichholz, mm)	19 x 19 / 25 x 25
Zahnkranzbohrfutter Kapazität (mm)	13
Max. Werkstückhöhe (mm)	195
Max. Meisselhub (mm)	200
Tischhub (längs / quer, mm)	400 / 100
Tischneigungsbereich	0 – 35°
Tischabmessungen (mm)	520 x 180
Werkstückanschlag (mm)	520 x 90
Max. Abstand Meisselmitte zum Anschlag (mm)	100
Abmessungen (mm)	650 x 500 x 1'760
Gewicht (kg)	125

LIEFERUMFANG

Unterschrank
 13mm Bohrfutter
 Bohrfutterschlüssel
 5/8" (15,87mm) Adapterhülse
 3/4" (19,05mm) Adapterhülse
 13/16" (20,64mm) Adapterhülse

1-3/16" (30,16mm) Adapterhülse
 2 Handradgriffe
 MDF Tisch
 Handhebel
 Werkstück Längsanschlag
 Bedienwerkzeug

