

PLANER / THICKNESSER 400V

JPT-F260-T



- Dual fold-out table to switch from planing to thicknessing in a matter of seconds, without removing the fence
- Graded planing tables made from high-quality cast iron guarantee outstandingly smooth workpiece movement
- The 3-knife shaft allows fast processing and top planing results
- Large-sized planer fence made from aluminium, inclinable to 45°, precisely machined, stable in operation
- Warp resistant one-piece machine casing for unfailing precision
- Feed can be turned off
- There is 2 emergency switches integrated on the machine for more security. One is near the main switch and the second one is on one side of planner table.
- Digital thickness readout included

TECHNICAL DATA

Motor (V / Kw)	400 V / 2,5 KW (3,3 hp) S1
Cutterhead rotation (rpm)	5000
Feed speed (m / min)	6,0
Maximum planing width (mm)	258
Thicknessing height (mm)	5 – 190
Maximum depth of cut (mm)	3,0
Maximum thicknessing depth of cut (mm)	4,5
Number of knives	3
Planer blades (mm)	260 x 25 x 3
Depth of cut table size (mm)	600
Planing table length (mm)	1100
Minimum thicknessing length (mm)	150
Fence size (mm)	1100 x 150
Fence tilt (deg.)	45° / 90°
Dust port (ø-mm)	100
Dimensions (mm) / Weight (kg)	1100 x 900 x 1000 / 202

Other technical data and accessories you will find in the manual. No liability is - taken for errors and printing errors. 25-06-2022 / C.Satter

PLANER / THICKNESSER 400V

JPT-F260-T



Accessories:



10000287: Set of 3 high speed steel (HSS) knives

Dimensions: 260 × 25 × 3 mm

Material: HSS



Other technical data and accessories you will find in the manual. No liability is - taken for errors and printing errors. 25-06-2022 / C.Satter